

Toro Vision II Plus Controllers

Toro Vision II Plus Controllers

Features

- Solid-state design with hybrid at-a-glance programming interface
- Non-volatile memory retains programming — even without batteries
- 9-volt NiCd battery provides 16-hour backup for current time
- Large LCD for easy programming
- 6, 9 or 12 stations
- Up to 3 start times per day
- Station run times:
- 1 to 90 minutes or 10 minutes to 9 hours (all stations)
- Two independent programs for lawn and shrub areas
- Programmable (A, B, or manual) Pump Start/Master Valve output
- 14-day programming, by day of week
- Interval programming — every day, every other day — up to 14 days between watering
- Watering Delay — 1- to 4-day program cancellation with auto resume
- Battery operation allows for Armchair Programming
- Global Season Adjust setting from 20% to 200% in 10% increments
- Automatic split-cycle mode when Season Adjust is great than 100%, prevents runoff
- Manual start of each station or entire program
- Built-in sensor port with manual override simplifies Rain Switch installation
- ProgramLink feature allows two Vision II Plus controllers to be linked sequential program operation
- Terminal strip hot post for easy valve actuation/identification
- System On/Off switch
- Fuse-protected circuitry
- Lockable, weather-resistant, wall-mount cabinet, (plastic/metal)
- Suitable for mounting outdoors



Imagine a controller that tells you what you need to know at a glance. Imagine a controller so simple to use that you actually use it.

- Individual station assignment (A or B) for quick and easy programming
- Larger LCD for easy programming and operation
- Front panel icons for easy programming
- On/Off switch for Rain Switch gives you increased control
- NiCd battery protects current time and day

Engineered with solid-state precision, this advanced hybrid, residential/light commercial controller combines exceptional versatility with user-friendly programming. So you don't have to imagine anymore.

Electric Specifications

Input power:

- 115/230V a.c. 50/60 Hz
- .12 amps (14 W) idle
- .30 amps (35W) maximum operating load

Output power: 24 V a.c.

- .50 amps (12 VA) per station
- .37 amps (9VA) per pump/master valve
- .90 amps (21 VA) total combined load
- UL listed, CSA certified

Mechanical Specifications

- Dimensions:
- Plastic: 14" H x 9 1/8" W x 3 1/4" D
- Metal: 13 1/2" H x 9 1/8" W x 3 3/4" D
- Main power in: 1/2" conduit access hole
- Valve power out: 1" conduit access hole

Ordering Information Toro Vision II Plus Controllers

Part #	Description	List Price	Ctn. Qty.
V2-P06E	6 Stations, Plastic Cabinet, Plug-in Transformer	180.00	1
V2-P09E	9 Stations, Plastic Cabinet, Plug-in Transformer	228.00	1
V2-P12E	12 Stations, Plastic Cabinet, Plug-in Transformer	305.00	1
V2-P06	6 Stations, Plastic Cabinet, Internal Transformer	180.00	1
V2-P09	9 Stations, Plastic Cabinet, Internal Transformer	228.00	1
V2-P12	12 Stations, Plastic Cabinet, Internal Transformer	305.00	1
V2-M06	6 Stations, Metal Cabinet, Internal Transformer	310.00	1
V2-M09	9 Stations, Metal Cabinet, Internal Transformer	368.00	1
V2-M12	12 Stations, Metal Cabinet, Internal Transformer	457.00	1